



SSQ-125-9A/B

Supplier / wholesaler/ wholesaler of 5"(125 mm) diamond cutting blades / circular saw blades for wall groove /granite



Min Order Quantity: 500 Pieces
 Supply Ability: 300,000 Pieces per month
 Payment Terms: T/T,L/C
 Price: To be negotiated

[Send email to us](#)

[Download To PDF](#)

Product Detail

Product Tags

Net Weight(g)	126g
Numbers of Teeth	9T
Teeth Height	12mm
Blade Diameter	5"(125mm)
Disc Bore Size	4/5"(22mm)
Blade Thickness	2.0-2.2mm
MAX.RPM	10000
Cutting Condition	Dry/Wet

The 5"(125mm) diamond saw blade leave minimal chipping while providing a fast, clean cut. It's the addition of quad holes makes this fantastic blade even more versatile.



Using the continuous blade with a flush cut or quad adapter allows you to do clean up and get into tight

space such as sink corners. Design the segment bond according to your different stone hardness, abrasiveness, machine, parameter to bring premium cutting and maximum output.

The technology of product formula is completely own, the process control is strict, the product price is high, the product category is complete. Diamond saw blade of cutting hard and brittle non-metallic materials has a high reputation in the industry.

The company has invested a large sum of money to purchase advanced high-precision and cutting-edge equipment in the industry, and has hired experts in the field of diamond powder metallurgy technology and factory application technical experts of diamond tools to do technical support. The company has adopted fine and new technology to provide civil industrial ceramics and power ceramics. Building decorative stone processing, stone carving and other fields of workers to provide more sharp, durable and time-saving diamond tools.

Our factory's strategy target is creating absolute quality advantage and satisfying customers' demand. All of our resource operation is centered on customer orientation. Only meeting customer requirement can make us strongly grow up and operation everlastingly. So we provide after-sale service: Professional engineer on line guide installation.

Features:

- 1.The saw blade has good sharpness and high efficiency at the process of cutting;
- 2.The saw blade can perfect high working performance without chip or breaking slates while cutting.
3. Working safe, quiet, and precise, reducing cutting & working time
4. Great adaptability & No chipping

Percentage of raw materials :

- High quality carbon structural steel matrix
- 65 manganese steel
- High grade diamond
- Intermediate or above quality
- Homemade alloy powder.

Application:

- The diamond grain of saw blade itself is coarse.brick concrete,
- Steel concrete wall groove

- All kinds of granite stone
- Other coarse
- Granular hard brittle non-metallic materials.

Using machine



Safety and working instructions

- Safety and working instructions for using diamond cutting pieces
- When installing or replacing the cutting piece, unplug the plug from the socket.
- Please choose the appropriate cutting piece according to the material to be processed.
- Cleaning flanges, shafts and cutting pieces.
- The flange shall be at least 1 / 3 of the diameter of the cutting piece
- The diameter of the shaft must be as large as the hole in the cutting piece.
- Do not privately increase the hole in the cutting piece.
- The direction of the arrow on the cutting piece and the steering of the machine must be caused by the direction of the arrow on the cutting piece and the steering of the machine.
- The maximum speed of the machine shall not be higher than the allowable maximum speed of the cutting piece.
- Can only do right angle or straight line cutting, engaging in curved angle cutting may cause section core fracture or section fracture.
- Avoid pressing the machine and hitting the material with the machine. Don't let the cutting piece overheat. Stop working at the right time to cool the cutting piece.
- Please remove the cutting piece when transporting the machine to avoid unnecessary damage.
- Wear protective goggles, industrial gloves, masks, safety shoes and work clothes when working.
- Protective cover, guide plate and vacuum must be used when working
- When doing wet cutting, isolation transformer must be used, and there must be a strong non-grounding socket on the isolation transformer.

FAQ

Q:Are samples available for quality test?

A: Yes, free samples can be prepared for quality test,and we bear the freight charges.

Q: Do you accept OEM Brand?

A: Yes,OEM Brand is accepted.We can also design label for you for free.

Q: Do you have any certificate?

A: Yes, we have MPA,ISO certificates .

Q:How could you ensure the quality?

A:Only high quality and stable batch products can ensure user's safety and consistent effect.To ensure this, all our products will pass the semi-product testing, finished- product testing and inspection before delivering.Quality passes only after 3 times testing.