

SSQ-156-12HA



Manufacturer/ Supplier/ Wholesaler of 6"(156mm) diamond cutting/ circular saw blades for concrete/ tile/ wall groove/ rock

Min Order Quantity: 500 Pieces
Supply Ability: 300,000 Pieces per month
Payment Terms: T/T,L/C,
Price: To be negotiated

[Send email to us](#)

[Download To PDF](#)

[Product Detail](#)

[Product Tags](#)

Net Weight(g)	232g
Numbers of Teeth	12T
Teeth Height	15mm
Blade Diameter	6"(156mm)
Disc Bore Size	7/8"(22.23mm)
Blade Thickness	2.2-2.4mm
MAX.RPM	10000
Cutting Condition	Dry/Wet

6" 156mm) granite stone cutting diamond circular saw blade.

High precision and ultra - thin cutting wheel is mainly used in the electronic information field all kinds of electronic components, optical glass and mechanical industry precision cutting and slotting. With a series of advantages such as high accuracy, kerf narrow, good surface quality, etc.



Resin bonded cutting blade has a low strength and heat resistance, but its self - sharp and good elasticity, and has a certain polishing performance. It is suitable for occasions such as high speed, cutting seam width and machining surface quality.

OUR ADVANTAGES:

- ✚ REAL FACTORY The quality is superior, yet the price is very reasonable.
- ✚ CUSTOM We provide OEM&ODM and inventory service.
- ✚ FREE SAMPLE We can provide free samples for you, please contact customer service.
- ✚ AFTER-SALES Our customer service is available 24 hours a day.
- ✚ SERVICE Please feel free to contact us if you have any questions.
- ✚ RICH EXPERIENCE Our more than 28 years of production and sales experience, professional foreign trade team.
- ✚ 5S MANAGEMENT We will be better for customers to provide quality products and services, believe us, is your right choice.

Why choose us

1. Professional producer of various diamond tools which contain diamond saw blade, cup wheel, dry drills, brazed saw blade, core bits, polishing pad etc.
2. To ensure the integrity of our products, we run our own production plants and cutting-edge research and development centers in china.
3. More than 20 years' experience of producing and selling the tools of diamond.

Package:

One piece in one PVC Double Blister, Paper Box or PVC Skin Card, More.

Delivery within 10work days after payment received, will be shipped by air, sea or express.

Free samples will be provided, feel free to get a sample.



Percentage of raw materials:

- High quality carbon structural steel matrix,
- 65 manganese steel,
- High grade diamond,
- Intermediate or above quality,
- Homemade alloy powder.

Application:

- Cut only concrete and wall grooves

Tool Compatibility

- Wall slot machine,
- cutting machine

Using machine



Safety and working instructions

- Safety and working instructions for using diamond cutting pieces
- When installing or replacing the cutting piece, unplug the plug from the socket.
- Please choose the appropriate cutting piece according to the material to be processed.
- Cleaning flanges, shafts and cutting pieces.
- The flange shall be at least 1 / 3 of the diameter of the cutting piece
- The diameter of the shaft must be as large as the hole in the cutting piece.
- Do not privately increase the hole in the cutting piece.
- The direction of the arrow on the cutting piece and the steering of the machine must be caused by the direction of the arrow on the cutting piece and the steering of the machine.
- The maximum speed of the machine shall not be higher than the allowable maximum speed of the cutting piece.
- Can only do right angle or straight line cutting, engaging in curved angle cutting may cause section core fracture or section fracture.
- Avoid pressing the machine and hitting the material with the machine. Don't let the cutting piece overheat. Stop working at the right time to cool the cutting piece.
- Please remove the cutting piece when transporting the machine to avoid unnecessary damage.
- Wear protective goggles, industrial gloves, masks, safety shoes and work clothes when working.
- Protective cover, guide plate and vacuum must be used when working
- When doing wet cutting, isolation transformer must be used, and there must be a strong non-grounding socket on the isolation transformer.

FAQ

Q:Are samples available for quality test?

A: Yes, free samples can be prepared for quality test,and we bear the freight charges.

Q: Do you accept OEM Brand?

A: Yes,OEM Brand is accepted.We can also design label for you for free.

Q: Do you have any certificate?

A: Yes, we have MPA,ISO certificates .

Q:How could you ensure the quality?

A:Only high quality and stable batch products can ensure user's safety and consistent effect.To ensure this, all our products will pass the semi-product testing, finished- product testing and inspection before delivering.Quality passes only after 3 times testing.