

SSS-130-9A/B



Supplier / wholesaler/ wholesaler of 5"(130 mm) diamond cutting blades / circular saw blades for wall groove /granite

Min Order Quantity: 500 Pieces
Supply Ability: 300,000 Pieces per month
Payment Terms: T/T,L/C
Price: To be negotiated

[Send email to us](#)

[Download To PDF](#)

Product Detail

Product Tags

Net Weight(g)	140g
Numbers of Teeth	9T
Teeth Height	15mm
Blade Diameter	5"(130mm)
Disc Bore Size	4/5"(22mm)
Blade Thickness	2.0-2.2mm
MAX.RPM	10000
Cutting Condition	Dry/Wet

The 5"(130 mm) diamond saw blades for wall groove and granite. Design the segment bond according to your different stone hardness, abrasiveness, machine, parameter to bring premium cutting and maximum output.



It's the addition of quad holes makes this

fantastic blade even more versatile. Segmented Diamond Blade provides the best cutting performance and long life for all of your projects. Use the segmented rim blade for fast and aggressive cuts on concrete, brick, block, stone, and stucco.

Using the continuous blade with a flush cut or quad adapter allows you to do clean up and get into tight space such as sink corners.

Our packaging methods are plastic packaging and paper packaging; This is the simplest and most economical way of packaging. Once you place an order, we will ship it as soon as possible. We also provide after-sales service. If you have any questions related to the product, please contact us in time

Increased operation time:

Diamond blade for angle grinder is constructed so that during operation it heats up more slowly which leads to an increase in operating time.

Durable:

Diamond angle grinder blade GRAFF can self-sharpen by erasing diamond grits during operation. For sharpening it is needed to make two or three cuts on silicon or abrasive stone.

HIGH SOLIDITY: Diamond blade for granite and stone is designed for precise cutting of concrete using small-sized angle grinders with 7/8" Arbor. This saw blade has a frame made of improved steel which ensures high solidity during operation.

Production capacity:

Our company have 5 large sets producing machines in our factory , and we are going to extend our production again. Now we can produce 10000pcs per day , and if your order quantity is big , we can arrange it at first.

Percentage of raw materials :

- High quality carbon structural steel matrix
- 65 manganese steel
- High grade diamond
- Intermediate or above quality
- Homemade alloy powder.

Application:

- The diamond grain of saw blade itself is coarse. brick concrete,
- Steel concrete wall groove
- All kinds of granite stone
- Other coarse
- Granular hard brittle non-metallic materials.

Tool Compatibility

- Stone cutting machine (marble machine)
- Angle grinder
- Bench cutting machine
- Wall slot machine is the main

Using machine



Safety and working instructions

- Safety and working instructions for using diamond cutting pieces
- When installing or replacing the cutting piece, unplug the plug from the socket.
- Please choose the appropriate cutting piece according to the material to be processed.
- Cleaning flanges, shafts and cutting pieces.
- The flange shall be at least $1/3$ of the diameter of the cutting piece
- The diameter of the shaft must be as large as the hole in the cutting piece.
- Do not privately increase the hole in the cutting piece.
- The direction of the arrow on the cutting piece and the steering of the machine must be caused by the direction of the arrow on the cutting piece and the steering of the machine.
- The maximum speed of the machine shall not be higher than the allowable maximum speed of the cutting piece.
- Can only do right angle or straight line cutting, engaging in curved angle cutting may cause section core fracture or section fracture.
- Avoid pressing the machine and hitting the material with the machine. Don't let the cutting piece overheat. Stop working at the right time to cool the cutting piece.
- Please remove the cutting piece when transporting the machine to avoid unnecessary damage.

- Wear protective goggles, industrial gloves, masks, safety shoes and work clothes when working.
- Protective cover, guide plate and vacuum must be used when working
- When doing wet cutting, isolation transformer must be used, and there must be a strong non-grounding socket on the isolation transformer.

FAQ

Q:Are samples available for quality test?

A: Yes, free samples can be prepared for quality test,and we bear the freight charges.

Q: Do you accept OEM Brand?

A: Yes,OEM Brand is accepted.We can also design label for you for free.

Q: Do you have any certificate?

A: Yes, we have MPA,ISO certificates .

Q:How could you ensure the quality?

A:Only high quality and stable batch products can ensure user's safety and consistent effect.To ensure this, all our products will pass the semi-product testing, finished- product testing and inspection before delivering.Quality passes only after 3 times testing.