

SSS-156-12A/B/C



Manufacturer/ Supplier/ Wholesaler of 6"(156mm) diamond cutting/ circular saw blades for concrete/ tile/ wall groove/ rock

Min Order Quantity: 500 Pieces
Supply Ability: 300,000 Pieces per month
Payment Terms: T/T,L/C,
Price: To be negotiated

 [Send email to us](#)

 [Download To PDF](#)

[Product Detail](#)

[Product Tags](#)

Net Weight(g)	225g
Numbers of Teeth	12T
Teeth Height	15mm
Blade Diameter	6"(156mm)
Disc Bore Size	7/8"(22.23mm)
Blade Thickness	2.2-2.4mm
MAX.RPM	10000
Cutting Condition	Dry/Wet

6"(156mm) Diamond Saw Blade Cutting Disc For Concrete Marble Masonry and Tile. Great premium diamond blade without busting the budget.

Smooth accurate cut for Granite, Quartz, and Engineered Stone.

Blades are known as Early Entry Blades and are designed for Green Concrete cutting on the same day the concrete is poured, without the concrete chipping or spalling.



Using Note:

- According to the saw blade to indicate the direction of rotation fastening installation, not reverse work.
- Dry cut, please do not cut for a long time, so as not to affect the life of the saw blade and cutting effect.
- Use wet slices should be added water, please do not curve cutting, cutting curve, please use the arc dedicated cutting film.
- Saw blade cutting, you must add water to cool, require water pressure greater than 0.1MPa.
- The optimum cutting time of concrete is 300-310 % hour for concrete, and the strength is 6-10Mpa.

Product Details

Precision sink design, smooth chip removal, damping and noise reduction, High hardness cutting segments, broad tooth lock life. Ultra-thin segments, precise cutting, extensive and no burrs.

Our special design for widen cutting head, it can increase the cutting efficiency, reduce the friction with tiles and stone, longer duration life and more sharpness, widely used in stone, marble, tiles, concrete, granite, the good performance will bring you very good using experience, and win widely good comments from our customers.

Packing & Delivery

diamond circular saw rotary cutter blade for dry cutting granite stone

Packing Details :flexible package

Delivery Details : 15-20 days after order



Percentage of raw materials:

- High quality carbon structural steel matrix ,
- 65 manganese steel,
- High grade diamond,
- Intermediate or above quality,
- Homemade alloy powder.

Application:

- Cut only concrete and wall grooves

Tool Compatibility:

- Wall slot machine,
- cutting machine

Using machine



Safety and working instructions

- Safety and working instructions for using diamond cutting pieces
- When installing or replacing the cutting piece, unplug the plug from the socket.
- Please choose the appropriate cutting piece according to the material to be processed.
- Cleaning flanges, shafts and cutting pieces.
- The flange shall be at least 1 / 3 of the diameter of the cutting piece
- The diameter of the shaft must be as large as the hole in the cutting piece.
- Do not privately increase the hole in the cutting piece.
- The direction of the arrow on the cutting piece and the steering of the machine must be caused by the direction of the arrow on the cutting piece and the steering of the machine.
- The maximum speed of the machine shall not be higher than the allowable maximum speed of the cutting piece.
- Can only do right angle or straight line cutting, engaging in curved angle cutting may cause section core fracture or section fracture.
- Avoid pressing the machine and hitting the material with the machine. Don't let the cutting piece overheat. Stop working at the right time to cool the cutting piece.
- Please remove the cutting piece when transporting the machine to avoid unnecessary damage.
- Wear protective goggles, industrial gloves, masks, safety shoes and work clothes when working.
- Protective cover, guide plate and vacuum must be used when working
- When doing wet cutting, isolation transformer must be used, and there must be a strong non-grounding socket on the isolation transformer.

FAQ

Q:Are samples available for quality test?

A: Yes, free samples can be prepared for quality test,and we bear the freight charges.

Q: Do you accept OEM Brand?

A: Yes,OEM Brand is accepted.We can also design label for you for free.

Q: Do you have any certificate?

A: Yes, we have MPA,ISO certificates .

Q:How could you ensure the quality?

A:Only high quality and stable batch products can ensure user's safety and consistent effect.To ensure this, all our products will pass the semi-product testing, finished- product testing and inspection before delivering.Quality passes only after 3 times testing.