

SSS-188-14A



Supplier/ wholesaler/ manufacturer of 7.5"(188mm) 14T diamond cutting blades/ saw blades /circular blades for groove/granite

Min Order Quantity: 500 Pieces
Supply Ability: 300,000 Pieces per month
Payment Terms: T/T,,L/C,
Price: To be negotiated

[Send email to us](#)

[Download To PDF](#)

Product Detail

Product Tags

Net Weight(g)	288g
Numbers of Teeth	14T
Teeth Height	13mm
Blade Diameter	7.5"(188mm)
Disc Bore Size	1"(25.4mm)
Blade Thickness	2.2mm
MAX.RPM	7200
Cutting Condition	Dry/Wet

The 7.5"188mm Diamond Saw Blades leave minimal chipping while providing a fast, clean cut. It's the addition of quad holes makes this fantastic blade even more versatile.



The diamond saw blade is forged by high quality carbon structural steel matrix, 65 Mn steel, high

grade diamond and self-made alloy powder. The unique segment design can improve the cutting efficiency and maximize the cutting efficiency.

Using the diamond saw blades with a flush cut or quad adapter allows you to do clean up and get into tight space such as sink corners. In the same environment, the blade is sharper and faster than the ordinary blade. It can ensure the cutting speed and efficiency.

We use high quality diamond. And more than 30 years of research and development experience. We are a manufacturer for diamond.

We based on excellent product quality, and endeavor to provide our clients with Three BETTER Concept: better products, better prices and better services. Our tenet is: no limit for best, only to make it better and better.

So far, our company has a total of about 150 employees, and we have been trying to provide customers with first-class products and comprehensive services. With the strictly controlled of production process, our products enjoy a high reputation in the industry.

Package: Paper and plastic

Segmented Blade: Continuous Rim Blade, Turbo Blade, Fine Turbo Balde, and Turbo Segmented Blade are available.

Cold-Press Sintered: Hot-Pressed Sintered, High-Frequency Welded, and Laser Welded are available.

Features:

1. Segmented rims provide maximum cutting life for products, and develop high-quality diamonds and unique bond matrix for fast aggressive cutting.
2. Very suitable for cutting concrete, brick, block, stone and plaster.
3. This product can be used for handheld saws, stone cutting machines and bench cutting machine.
4. This product can be dry cut or wet cut.

Percentage of raw materials :

- High quality carbon structural steel matrix
- 65 manganese steel
- High grade diamond
- Intermediate or above quality
- Homemade alloy powder.

Application:

- all kinds of granite stone
- other hard brittle non-metallic materials.

Tool Compatibility

- Handheld saws,
- Stone cutting machines
- Bench cutting machine

Using machine



Safety and working instructions

- Safety and working instructions for using diamond cutting pieces
- When installing or replacing the cutting piece, unplug the plug from the socket.
- Please choose the appropriate cutting piece according to the material to be processed.
- Cleaning flanges, shafts and cutting pieces.
- The flange shall be at least 1 / 3 of the diameter of the cutting piece
- The diameter of the shaft must be as large as the hole in the cutting piece.
- Do not privately increase the hole in the cutting piece.
- The direction of the arrow on the cutting piece and the steering of the machine must be caused by the direction of the arrow on the cutting piece and the steering of the machine.
- The maximum speed of the machine shall not be higher than the allowable maximum speed of the cutting piece.
- Can only do right angle or straight line cutting, engaging in curved angle cutting may cause section core fracture or section fracture.
- Avoid pressing the machine and hitting the material with the machine. Don't let the cutting piece overheat. Stop working at the right time to cool the cutting piece.
- Please remove the cutting piece when transporting the machine to avoid unnecessary damage.
- Wear protective goggles, industrial gloves, masks, safety shoes and work clothes when working.
- Protective cover, guide plate and vacuum must be used when working
- When doing wet cutting, isolation transformer must be used, and there must be a strong non-grounding socket on the isolation transformer.

FAQ

Q:Are samples available for quality test?

A: Yes, free samples can be prepared for quality test,and we bear the freight charges.

Q: Do you accept OEM Brand?

A: Yes,OEM Brand is accepted.We can also design label for you for free.

Q: Do you have any certificate?

A: Yes, we have MPA,ISO certificates .

Q:How could you ensure the quality?

A:Only high quality and stable batch products can ensure user's safety and consistent effect.To ensure this, all our products will pass the semi-product testing, finished- product testing and inspection before delivering.Quality passes only after 3 times testing.